


ILCZ1

Luminaire

CITIZEN SOFT



Decorative or functional luminaire ideal for residential areas (green spaces, pedestrian areas, parks...). Extensive optical and light distributions, glare control and cut-off suitable for pedestrians. Excellent relation between efficiency and cost.

MAIN FEATURES:

High efficiency. Up to 142 lm/W net
From 20W to 80W
Anti-glare cut-off
Exclusive design
18 light distribution curves
Zhaga Standard (Book 15)
Ready 4IoT. Ready for any intelligent lighting control solution.

APPLICATIONS:

Residential Streets (Zones 30)
Pedestrian Zones
Commercial and Tourist Streets
Squares
Green Areas; Parks and Gardens

[Project sheet](#) | [CAD](#) | [Catalogue](#) | [Mounting instructions](#) | [BIM](#) | [HD image](#)


BENITO

info@benito.com
tel. 93 852 1000

SPECIFICATIONS :

Housing material:	High pressure die-cast aluminium EN AC-43000, EN AC-43100, EN AC-43400, EN AC-44100, EN AC-47100 according to the UNE EN 1706 standard
Diffuser (optic system enclosure):	High-quality polycarbonate diffuser. Lifelong transparency
Fixing elements:	Stainless Steel 18/8 - AISI 304
Housing:	Light polycarbonate structure covered in aluminium which houses the LED module and driver
Sealing gaskets:	Silicone foam
IP rating (luminaire):	66
IP rating (optic system):	66
IK rating (impact resistance):	10
LEDs thermal dissipation:	Thermal dissipation through finless luminaire body, without conductive fluids. Passive convection dissipation ensuring thermal contact with the LED modules through a high-conductivity thermal transfer material
Anti-condensation valve:	
Paint and finishes:	Polyester powder paint coating, electrostatically sprayed and sublimated in the oven. Resistant to corrosion
Colour:	RAL 9006. Optional: other colours
Mounting:	Top Ø60mm
Tilt range:	
Maintenance:	Fast connector IP67. Modular concept for easy component replacement: LEDs, drivers, SPD
Recommended mounting height:	3 - 6 m
Driver:	Constant current adjustable and programmable driver. Embedded in the luminaire, pre-wired on a galvanised steel plate
Flow Reduction:	Dimmable driver 0-10V. Programmable on 5 levels. Optional: DALI 2. Includes the characteristics of Wireless, AOC, MTP, DTL
Ready4IOT - Connectivity:	- Autonomous multiple-level dimming or virtual midnight - Ready4IoT - Dimming by main voltage - Line switch
Surge protection device (SPD):	Type 2, 10kV and 20kA transient surge protector. Series connection with thermofuse disconnecter for a more effective protection at the end of its service life


DRAWING:



INSTALLATION:




V. 2024-01-08 | The constant improvement and evolution of our products may result in some modifications of the technical specifications and characteristics of the products without prior notice.




TECHNICAL DATA:

	REF.	N° LEDs	Power W	I Driver mA	Real luminous flux (T) =85°C		Initial luminous flux (T) =25°C	
					Flux lm	Efficacy lm/W	Flux lm	Efficacy lm/W
CITIZEN SOFT	ILCZ1	16	20	375	2842	142	3240	162
		16	30	563	4242	141	4836	161
		16	40	750	5600	140	6384	160
		32	40	375	5680	142	6475	162
		32	60	563	8400	140	9576	160
		32	80	750	11040	138	12586	157

Luminous flux and efficiency at 4000°K and CRI>70.
Luminous flux tolerance < +/-3%.
Values may be subject to changes due to LED binning.



PHOTOMETRY:



*Show 4 recommended lighting distributions. Refer to the 18 typologies.

V. 2024-01-08 | The constant improvement and evolution of our products may result in some modifications of the technical specifications and characteristics of the products without prior notice.

LEDs MODULE:

LEDs module:	BENITO-NOVATILU Zhaga standard for 8 and 16 LEDs. Check colour temperature, CRI and light distributions		
Replaceable module:	Yes		
LED:	5050		
Number of LEDs:	16 - 32		
PCBs format:	2 o 4 Zhaga (Book 15) 2x4		
LED nominal efficacy:	172 lm/W		
Colour temperature:	PC Amber, 2K2, 2K7, 3K, 4K, 5K		
Colour rendering index CRI:	>70 (optional >80)		
Average LED useful time L90B10:	L90B10 >100.000 horas		

OPTIC SPECIFICATIONS:

Optic system:	PMMA lenses 2x2		
Light distributions:	18 light distribution curves		
Upward light output ratio ULOR:	<1%		
Downward light output ratio DLOR:	>99%		
Glare index:	Between D5 and D6 (depending on the light distribution)		
Luminous intensity category:	Between G*4 and G*6 (depending on the light distribution)		
Luminous flux CIE n°3:	>95%		
Photobiological safety:	RG0 (exempt of risk)		
Initial luminous flux Tj=25°C (up to):	lm	10698	
Initial luminaire efficacy Tj=25°C (up to):	lm/W	138	
Real luminous flux Tj=85°C (UNE EN 13032-4) (up to):	lm	9384	
Real luminaire efficacy Tj=85°C (UNE EN 13032-4) (up to):	lm/W	121 (Rendimiento = 82.6 % lm/W (Real 85°C) ÷ lm/W (Nominal Led))	

ELECTRIC SPECIFICATIONS:

Nominal maximum power (LEDs):	W	72
Maximum power consumed (luminaire):	W	80
Power range:	W	20-80W
Maximum current of LED:	mA	<400 (<50% I _{max})
Power supply protection classes IEC:	Class I and II	
Surge protection device (SPD):	Type 2, 10kV and 20kA transient surge protector. Series connection with thermofuse disconnecter for a more effective protection at the end of its service life	
Common and differential mode protection (SPD) U _{dc} :	kV	10 con NTC opcional
Max current (8/20) (SPD):	kA	20
Thermal phase disconnection (SPD):	Yes	
Input voltage:	Vac	220-240
Input voltage (max rate):	Vac	198-264
Input frequency:	Hz	47-63
Starting current:	A	<65
Duration of the starting voltage peak:	ms	<0,3
Driver efficacy:	>90%	
Power factor 100% consumption:	>0,98	
Power factor 50% consumption:	>0,95	
Total harmonic distortion (THD):	<10	
Power consumption on standby mode:	W	<0,4
Energy class:	A++ IPEA>1,15	

OPERATING CONDITIONS:

Average LED useful time L90B10:	>100.000	
Average driver useful life to Tp <70°C:	100.000	
Average luminaire useful life L90B10 (TM-21):	72.167	
Ambient temperature (Ta):	°C	de -35°C a +50°C
Aerodynamic resistance (CxS):	m2	0,082
Vibration test (15Hz 3 axis):		
Guarantee:	years	5 years (extensible up to 10 years)

PACKAGING DIMENSIONS:

Net weight	kg	5,5
Gross weight	kg	7
Luminaire dimensions (LxWxH)	mm	500x500x395
Packaging dimensions (LxWxH)	mm	
Pieces per box		1
Quantity per container 20ft		
Quantity per container 40ft		

CERTIFICATES:

Security certificates:	EN 40 / EN 62031 / EN 62493 / EN 62471 / IEC 62778 / EN 61247-2-13"		
EMC certificates:	EN 55015 / EN 61547 / EN 61000-3-2 / EN 61000-3-3 / EN 61347-2-13 / EN 61347-1 / EN 62384"		
Other certifications:	IEC 62262 / EN 13032-4 / EN 62717 / EN 6272-1 / EN 6272-2-1 / EN 61643-11		

Company Certifications



BENITO

info@benito.com
tel. 93 852 1000

V. 2024-01-08 | The constant improvement and evolution of our products may result in some modifications of the technical specifications and characteristics of the products without prior notice.